SURFACE MOUNT CRYSTAL OSCILLATOR FCXO-03L



Features

- Compact design
  (5.0mm×3.2mm×1.2mm Max., Weight : 0.07g).
- Resin sealed ceramic package assures extreme accuracy and high reliability.
- Lead-free soldering is available.
- Applications : Laptop PC, DSC, DVC, W-LAN

Specifications

Item	Standard specifications		
Frequency range(MHz)	1.5 to 60.0		
Frequency tolerance (ppm)(at 25°C)	15, ±20, 30, ±50, ±100		
Storage temperature range(°C)	−40 to +85		
Operating temperature range(°C)	−10 to +60	−20 to +70	−40 to +85
Frequency versus temperature characteristics(ppm) (Refer to 25°C)	±30 50 ±100	±30 50 ±100	±50 ±100
Supply voltage(V)	3.3 0.33, 3.0±0.3, 2.5±0.25		
Current consumption (mA)	6(Typ.), 15(Typ.) (Depends on frequency and fan out)		
Output level	CMOS, TTL		
Symmetry(%)	50 10, 50±5		

"Stand-by" CTRL table

Stand-by	Output
"H"	Output enabled.
"L"	Oscillation stop and High impedance output.

- Bypass capacitor should be connected between V_{DD} and GND due to the stabilized operation for the crystal oscillator.
- Please consult us for customized specifications.
  All specifications and markings subjected to change without notice.

Dimensions

Unit mm



Taping

Unit : mm



Quantity : 1000 pieces Max./Reel

RIVER URL http://www.river-ele.co.jp

Head Office	2-1-1 Fujimigaoka Nirasaki Yamanashi Japan Phone 81-551-22-1211 Fax 81-551-22-6645	River Electronics(Singapore)Pte.Ltd	Phone 65-6258-7874	Fax 65-6258-7366
Tokyo Office	4-40-14 Nishishinjuku Shinjuku-ku Tokyo Japan Phone 81-3-3377-5444 Fax 81-3-3374-2865	Taiwan River Co.,Ltd.	Phone 886-2-8988-2811	Fax 886-2-2983-4785
Osaka Office	Phone 81-6-6998-4888 Fax 81-6-6998-4899	Xi'an River Electronics Corporation	Phone 86-29-88697274	Fax 86-29-88635134